

Environex

Sustainable solutions with chemistry



The Next Generation in Specialty Formulators



Quality
ISO 9001
SAI GLOBAL



Synergy

15 YEAR WARRANTY

CSIRO TESTED Consolidator/Penetrating Sealer

SYNERGY is a world class combination consolidator and penetrating sealer specially formulated for superior stain and salt protection around swimming pools. **SYNERGY** is suitable for internal, external, domestic and commercial surfaces and will prevent permanent staining from most common spills.

To minimize the effects of salt attack **ENVIRONEX** recommends installing a 40mm overflow pipe located approximately 150mm beneath the pool coping. This will remove the chance of the coping being regularly submersed in the corrosive pool water environment.



Always wear Personal Protective Equipment (PPE) – A minimum requirement of Safety Glasses, Gloves & Boots. Damage to clothing may occur.

- Do not seal under 10°C or over 30°C.
- Apply a minimum of 2 coats of **SYNERGY** to a clean dry surface with an **ENVIRONEX LAMBSWOOL APPLICATOR** or **ENVIRONEX VITON SEAL SPRAYER**. **SYNERGY** may take 2 to 3 days to dry. **ENVIRONEX** recommend dip sealing your coping pavers/tiles with **SYNERGY**. Porous masonry will require more coats (3-5) of **SYNERGY** to provide adequate protection. Allow minimum 7 days curing.
- Only use **REFRESH** pH neutral detergent for daily or weekly maintenance.
- Not suitable for Bluestone.
- **ENVIRONEX** recommend resealing the pool surrounds every 2-3 years to assist in prevention of Salt Attack.
- **Always test first.**



19 Motivation Dr, Wangara WA 6065, AUSTRALIA

T +61 9302 4000 | FREE 1900 999 196 | F +61 8 9302 5000 | W environex.net.au