

# PORCELAIN & QUARTZ SEALER

PREVIOUSLY KNOWN AS PORCELAIN PLUS™

Porcelain & Quartz Sealer is a premium, impregnating sealer specifically designed for porcelain and quartz surfaces. Porcelain & Quartz Sealer features nano size sealing molecules that will seal the micro pores in polished porcelains and quartz surfaces. This technology has been developed specifically for surfaces with low absorption rates in an easy to use, non-film forming sealer.



## TYPICAL APPLICATIONS

Porcelain & Quartz Sealer was specifically designed for porcelain and quartz surfaces.

## BENEFITS

- Seals micro pores in polished, honed or textured porcelain and quartz surfaces
- Creates a unique molecular bond
- Permanent, long lasting protection
- Repels oil and water based stains
- Non-film forming and invisible
- Holds up to commercial cleaners and cleaning equipment
- Will not change the coefficient of friction (COF) of the surface
- Suitable for indoor, outdoor, residential and commercial use
- 10-Year Performance Warranty will protect:
  - ◇ Quartz Surfaces
  - ◇ Polished and Semi-Polished Porcelains
  - ◇ Through Body Porcelains
  - ◇ Textured Porcelains
  - ◇ Glazed, Matte and Multi-Glazed Porcelains
  - ◇ Grout Joints for all Porcelain and Glazed Ceramic Tile Installations

## CONTENTS

Ethanol, silane, fluoropolymer.

## PACK SIZE

32 fl OZ / .95 L | 110600

## HOW TO USE

1. TEST PRODUCT ON A SMALL, INCONSPICUOUS AREA FIRST. Allow a 24-hour cure time to determine the ease of application and desired results.
2. Apply when surface temperature is between 40 - 95°F (5 - 35°C). Surface must be dry, clean and free of residues.
3. DO NOT thin product
4. Application rates: 200 – 300 sf/qt if using STAIN-PROOF™ Porcelain & Quartz Sealer as a two-coat process that includes pre-sealing prior to grouting. 400 – 500 sf/qt if sealing a finished, grouted installation or quartz countertop. Visit stain-proof.com for our coverage chart.
5. Generously apply STAIN-PROOF™ Porcelain & Quartz Sealer using low pressure hand sprayer or lambwool applicator pad. Surfaces should have a mirror like 'wet' look for 30 seconds. Avoid contact with surrounding areas. Wait for approximately 20 minutes, but, before the surface dries, polish the surface thoroughly with clean, dry, micro fiber towels or similar, to remove any excess sealer. Moistening cloth with STAIN-PROOF™ Porcelain & Quartz Sealer will ease polishing. Wait 24 hours to grout; this allows for the proper chemical bonding of STAIN-PROOF™ Porcelain & Quartz Sealer to the porcelain's surface. Once grout has cured, the second coat may be applied following the same techniques used for the first coat.
6. If sealing a finished and grouted installation or Quartz countertop, follow the application techniques listed in step #5, only applying one liberal coat of Porcelain & Quartz Sealer.
7. Use an organic solvent e.g. denatured alcohol to clean equipment.

NOTE: Sealer will NOT prevent surface etching, scuff marks or wear and may lighten or darken some surfaces. Spills should be cleaned up immediately to minimize absorption.

## VOC CONTENT

VOC (CALCULATED): <570 g/L

## COUNTRY OF MANUFACTURE

Made in the USA with globally sourced materials.

## WARRANTY



\*A 10-YEAR PERFORMANCE WARRANTY is offered when product applied by an Accredited Applicator following our written instructions and surface is maintained regularly using our written maintenance system, as outlined in our warranty document. Visit our website at [www.stain-proof.com](http://www.stain-proof.com) to find your nearest accredited applicator.



FOR MORE INGREDIENT INFORMATION, TECHNICAL DOCS, APPLICATION TIPS & COVERAGE GUIDE, SCAN THIS CODE OR VISIT: [STAIN-PROOF.COM](http://STAIN-PROOF.COM)



150 Dascomb Rd,  
Andover, MA 01810  
USA  
1866 667 5119

30-32 Assembly Drive  
Tullamarine, Vic, 3043  
Australia  
1800 786 617

## STORAGE

Store in a well ventilated place. Keep container tightly closed. Keep cool and locked up. IN CASE OF Fire: Use alcohol resistant foam or normal protein foam for extinction

## DISPOSAL

Dispose of contents in accordance with applicable local/national/regional/international regulations.

## APPLICATION NOTES

1. Porcelain & Quartz Sealer is a one coat process.
2. When using as a pre-sealer to help with removing excess grout, apply Porcelain & Quartz Sealer as directed in step #5 above.
3. Once the grout has cured, the grout may then be sealed. Check with the grout manufacturer for grout cure times. Coverage for 1/4" grout joints is 1,200 linear ft/qt and for 1/8" grout joints is 2,400 linear ft/qt. Excess sealer is easily removed.
4. IMPORTANT REMINDER: When sealing grout with Porcelain & Quartz Sealer, your grout will repel stains from both water and oil-based materials.

## CAUTIONS

**DANGER:** Highly flammable liquid and vapor. Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. Suspected of causing genetic defects. Harmful to aquatic life with long lasting effects. **PRECAUTIONS:** Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces- No smoking. Avoid breathing mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after using. Use only outdoors or in a well ventilated area. KEEP OUT OF REACH OF CHILDREN.

## FIRST AID

If exposed or concerned get medical advice. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs get medical advice. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped give artificial respiration. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF SWALLOWED: Immediately call a poison center or doctor.

## COVERAGE GUIDE

Surface Type	sq ft/qt**	m <sup>2</sup> /L**
Porcelain - Honed and Polished	400	40
Quartz	400	40

\*\* Minimum Coverage rates as each surface has different absorption rates. Check with your supplier



150 Dascomb Rd,  
Andover, MA 01810  
USA  
1866 667 5119

30-32 Assembly Drive  
Tullamarine, Vic, 3043  
Australia  
1800 786 617