S	SAE 30 – 4 STROKI	E ENGINE O	IL
	SAFETY DATA		
MSDS No: Product Name:	SAE 30 - 4 STROKE ENGINE OIL		JICK SMART PRODUCTS 53 ASSEMBLY DRIVE LLAMARINE VIC 3043
Manufacturers Code:	SAE1, SAE5, SAE20	Ph: (03) 933	ABN: 40 959 725 049 8 6655 (BH) Fax: (03) 9335 2598
Date:	September 2020		Email: <u>gsmart@bigpond.net.au</u> ww.quicksmartproducts.com.au
1. IDENTIFICATION	OF THE MATERIAL AND SUPPLIER		
Product Name	SAE 30 - 4 STROKE ENGINE OIL		
Company Name	QUICK SMART PRODUCTS		
Address	53 Assembly Drive Tullamarine Vic 3043		
Telephone	(03) 9338 6655 (BH) Poisons Inform	nation Centre 131126	(03) 9336 7945 (AH)
Recommended Use	Engine Oil recommended for all 4 str	oke small engines.	
2. HAZARDS IDENT	IFICATION		
Hazard Classification	Not hazardous		
Dangerous Goods Classification	Not Dangerous Goods according to t of Dangerous Goods by Road & Rail		an Code for the Transport
GHS Label Elements			
Signal Word	Not Applicable		
Symbol(s)	Not Applicable		
Hazard Statements	Not Applicable. No known significant	Not Applicable. No known significant effects or critical hazards.	
Precautionary Statem	ents		
Prevention	Not Applicable		
Response	Not Applicable		
Storage	Not Applicable		
Disposal	Not Applicable		
Other Hazards which do not result in classification	Defatting of the skin.		
3. COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical Entity	CAS	lo	Proportion
Refined Mineral Oil. (A ca Paraffinic, Napthenic & A Complex mixture of addit	romatic Hydrocarbons) NA		VHIGH > 80% LOW < 10%

SAE 30 – 4 STROKE ENGINE OIL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	SAE 30 - 4 STROKE ENGINE OIL	53 ASSEMBLY DRIVE
		TULLAMARINE VIC 3043
Manufacturers Code:	SAE1, SAE5, SAE20	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
Date:	September 2020	Email: <u>gsmart@bigpond.net.au</u>
240.	000000000000000000000000000000000000000	Web: www.quicksmartproducts.com.au

4. FIRST AID MEASURES

Description of necessary measures according to routes of exposure

Ingestion	Rinse mouth out with water. Do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side to maintain open airway to prevent aspiration. If irritation develops or persists or vomiting has occurred after ingestion, seek immediate medical assistance.
Eye Contact	In case of eye contact, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a Doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation persists seek medical advice/attention.
Skin Contact	If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair with soap and water. If irritation or rash occurs seek medical advice/attention.
Inhaled	If affected, remove the affected person from further exposure into fresh air, if safe to do so. Lay patient down in a well ventilated area. Allow patient to assume most comfortable position and keep warm. If experiencing respiratory symptoms, seek immediate medical advice/attention. If not breathing, provide artificial respiration and seek immediate medicate medical assistance. If irritation develops or persists, consult a Doctor.
First Aid Facilities	Eye wash station and safety showers are recommended in the area where the product is used.
Protection for First Aiders	No action shall be taken involving any personal risk or without suitable training.

Most Important Symptoms & Effects, Both Acute & Delayed, Caused by Exposure

See Section 11 for more detailed information on health effects and symptoms.

Advice to Doctor: Treat symptomatically based on individual reactions of patient and judgment of doctor.

5. FIRE FIGHTING MEASURES

General Measures	Do not enter enclosed or a confined work space without proper protective equipment. Fire fighting personnel should wear respiratory protection (positive pressure if available). Clear fire area of all non-emergency personnel. Stay upwind. Keep out of low areas. Eliminate ignition sources. Move fire exposed containers from fire area if it can be done without risk.
Flammability Conditions	Product is a combustible liquid (C2). Product will burn if involved in a fire.
Extinguishing Media	Use extinguishing media appropriate for surrounding fire. Use carbon dioxide, foam, dry chemical or water spray.
Unsuitable Extinguishing Media	Do not use water jet as an extinguisher, as this will spread the fire.
Combustion Hazards	On combustion may produce smoke, carbon dioxide and hazardous gases, which include carbon monoxide.
Explosion	No information to indicate that the product is an explosion hazard. Closed containers may explode when exposed to extreme heat.

S	AE 30 – 4 STROKI SAFETY DATA	
MSDS No: Product Name:	SAE 30 - 4 STROKE ENGINE OIL	QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE TULLAMARINE VIC 3043
Manufacturers Code:	SAE1, SAE5, SAE20	ABN: 40 959 725 049 Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
Date:	September 2020	Email: <u>gsmart@bigpond.net.au</u> Web: www.quicksmartproducts.com.au
Personal Protective Equipment	Fire fighters should wear a positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots and gloves).	
Flash Point	>230°C (Typical)	
Hazchem Code	Not applicable.	
6. ACCIDENTAL RE	LEASE MEASURES	
General Response Procedure	Avoid accidents, clean up immediately. Slippery when spilled. Avoid contact with eyes and skin. Eliminate all sources of ignition. Increase ventilation. Use clean, non-sparking tools and equipment.	
Containment	Stop the leak if safe to do so. Isolate the danger area. Contain the spill and absorb with a proprietary absorbent material, sand or earth.	
Clean Up Procedures	Having contained the spill, collect all material and place used absorbent in suitable, labelled containers for disposal. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water to enter drains, surface water, sewers or water courses.	
Environmental Precautionary Measures	Use appropriate containment to avoid environmental contamination. Do not let product enter drains, surface water, sewers or water courses. Advise local authorities if this occurs.	
Evacuation Criteria	Evacuate personnel to safe areas.	
Personal Precautionary	Small Spills - Wear Nitrile gloves, glasses/goggles, boots and full length clothing. If mists of vapour are generated, an approved organic vapour/particulate respirator is required.	
Measures		A full chemical resistant bodysuit is recommended ed for oxygen deficiency. If in doubt about oxygen ing apparatus.
Disposal	Dispose of waste in accordance to Fe into sewer system is not permitted.	ederal, EPA, State and Local Regulations. Disposal
7. HANDLING AND S	STORAGE	
Safe Handling	with the product by using appropriate boots and full length clothing. Eating, area where this material is handled, s hygiene practices and recommended	er are available and ready for use. Avoid contact protective equipment such as gloves, goggles, drinking and smoking should be prohibited in the stored and processed. Observe good personal procedures. Wash thoroughly after handling. Take c discharges by bonding and grounding equipment.
Safe Storage	ventilated area out of direct sunlight a foodstuffs and clothing. Do not store closed when not in use. Containers th	hat will burn if involved in a fire. Store in a dry, well and away from ignition sources, oxidising agents, in unlabelled containers. Keep containers tightly nat have been opened must be carefully resealed Inspect regularly for deficiencies such as damage

SAE 30 – 4 STROKE ENGINE OIL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	SAE 30 - 4 STROKE ENGINE OIL	53 ASSEMBLY DRIVE
		TULLAMARINE VIC 3043
Manufacturers Code:	SAE1, SAE5, SAE20	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598 Email: gsmart@bigpond.net.au
Date:	September 2020	Web: www.quicksmartproducts.com.au

8. **EXPOSURE CONTROL** Occupational No exposure standards have been established for this product. However, in the **Exposure Limits** operation of certain equipment or at elevated temperatures, if oil mists or aerosols are generated the following Exposure Standard should be observed: TWA: 5mg/m³ STEL: 10mg/m³ (ACGIH) **Biological Limit** No data available **Engineering Controls** Special ventilation is not normally required when using this product at normal temperatures. In the operation of certain equipment, at elevated temperatures or in confined spaces, mist or vapour may be generated and local exhaust ventilation should be used to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. **Respiratory Protection** If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices. **Eye Protection** Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standards AS/NZS 1337 - Eye Protectors for Industrial Applications. Hand Protection Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1 - Occupational Protective Gloves - Selection, Use and Maintenance. **Body Protection** During normal operating procedures, long sleeved clothing is recommended to avoid skin contact. Chemical resistant plastic apron is recommended where large quantities are handled.

PHYSICAL AND CHEMICAL PROPERTIES 9.

Physical State	Liquid
Appearance	Red oily liquid
Odour	Characteristic lubricating oil odour
рН	No data available
Melting/Freezing Point	No data available
Initial Boiling Point	No data available
Boiling Range	No data available
Flash Point	>230°C (Typically)
Evaporation Rate	No data available
Flammability Limits	No data available

SAE 30 – 4 STROKE ENGINE OIL SAFETY DATA SHEET		
MSDS No: Product Name:	SAE 30 - 4 STROKE ENGINE OIL	QUICK SMART PRODUCTS 53 ASSEMBLY DRIVE
Manufacturers Code:	SAE1, SAE5, SAE20	TULLAMARINE VIC 3043 ABN: 40 959 725 049 Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
Date:	September 2020	Email: <u>gsmart@bigpond.net.au</u> Web: www.quicksmartproducts.com.au
Vapour Pressure	<0.0005 kPa (expected @ 20°C)	
Vapour Density	>1 (Air = 1)	
IBP	>280°C	
Specific Gravity	@ 15°C 0.89	
Solubility in Water	Insoluble	
Auto-Ignition Temp	>320°C (Typically)	
LEL	Typically 1% v/v	
UEL	Typically 10% v/v	
Viscosity (cSt@40°C)	Not available	
10. STABILITY AND REACTIVITY		

Reactivity	This product does not pose any further reactivity hazards other than those listed below.
Stability	Stable under recommended storage and handling conditions (refer Section 7).
Conditions to Avoid	Avoid direct contact with sunlight, heat, flames, sparks etc.
Materials to Avoid	Strong oxidising agents. Heat or high temperatures.
Hazardous Decomposition Products	Hazardous decomposition products are not expected to form during normal storage and use. See Section 5 for Hazardous Combustion Products.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	The product is a mixture and test data is not available for the product as a whole.
Likely Routes of Exposure:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Potential Acute Health I	Effects
Eye Contact	No known significant effects or critical hazards.
Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Skin Contact	Defatting to the skin. May cause dryness and irritation.
Ingestion	No known significant effects or critical hazards.
Symptoms Related to the	ne Physical, Chemical and Toxicological Characteristics
Eye Contact	No specific data.
Inhalation	May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Skin Contact	Adverse symptoms may include the following: Irritation Dryness Cracking
Ingestion	No specific data.

SAE 30 – 4 STROKE ENGINE OIL SAFETY DATA SHEET QUICK SMART PRODUCTS

MSDS No:		QUICK SMART PRODUCTS
Product Name:	SAE 30 - 4 STROKE ENGINE OIL	53 ASSEMBLY DRIVE
		TULLAMARINE VIC 3043
Manufacturers Code:	SAE1, SAE5, SAE20	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598 Email: <u>gsmart@bigpond.net.au</u>
Date:	September 2020	Web: www.quicksmartproducts.com.au

Delayed and Immediate Effects and also Chronic Effects from Short and Long Term Exposure

Potential risk of transient stinging or redness if accidental eye contact occurs.
Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Ingestion of large quantities may cause nausea and diarrhoea.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.
Used oils may contain harmful impurities that can accumulate during usage. Due to the use of oils in different types of equipment the type of impurities that accumulate during its usage are unknown. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. All used oil should be handled with caution and skin contact avoided as far as possible by wearing suitable gloves, such as those made of nitrile rubber.

12. ECOLOGICAL INFORMATION

There is no data available for this product as a whole.
Based on the components and similar products the product is not expected to be readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
Floats on water. If it enters soil, it will absorb onto soil particles and will not be mobile.
No information is available on bioaccumulation for this product.
Do not allow product to reach water ways, drains or sewers. Product will float on water. Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	The generation of waste should be avoided or minimised wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any
	regional local authority requirements. Waste packaging should be recycled. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SAE 30 – 4 STROKE ENGINE OIL SAFETY DATA SHEET

MSDS No:		QUICK SMART PRODUCTS
Product Name:	SAE 30 - 4 STROKE ENGINE OIL	53 ASSEMBLY DRIVE
		TULLAMARINE VIC 3043
Manufacturers Code:	SAE1, SAE5, SAE20	ABN: 40 959 725 049
		Ph: (03) 9338 6655 (BH) Fax: (03) 9335 2598
Date:	September 2020	Email: <u>gsmart@bigpond.net.au</u> Web: www.guicksmartproducts.com.au
		web. www.quicksmartproducts.com.au

Special Precautions Contact a specialist disposal company or the local waste regulator for advice. **for Landfill**

14. TRANSPORT INFORMATION

Transport Regulations

Not classified as dangerous for transport (ADG, IMDG, IATA)

Special Precautions for User

No known special precautions required.

15. REGULATORY INFORMATION

A poison schedule has not been allocated for this product.

AICS (Australia) All ingredients are listed in the Australian Inventory of Chemical Substances (AICS)

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

SUSMP

16. OTHER INFORMATION

|--|

Date of Preparation or SDS reviewed: 3 September 2020 last revision of SDS

Abbreviations	
ADG Code	Australian Code for the Transport of Dangerous Goods by Road & Rail
ACGIH	American Conference of Governmental Industrial Hygienists
IMDG	International Maritime Dangerous Goods
ΙΑΤΑ	International Air Transport Association
CAS Number	Chemical Abstracts Service Registry Number
TWA	Time Weighted Average
STEL	Short Term Exposure Limit
HAZCHEM Code	Emergency action code of numbers and letters which gives information to emergency
	services
GHS	Globally Harmonised System of Classification and Labelling
SUSMP	Standard for the Uniform Scheduling of Drugs and Poisons
AICS	Australian Inventory of Chemical Substances
NOHSC	National Occupational Health and Safety Commission

This SDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user must review this SDS in the context of how the product will be handled in the workplace and in conjunction with other materials. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. It clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company.

END OF SDS