

PRODUCT DATA SHEET

Food Grade Synthetic Hydraulic Oil ISO 68, 5 Gal

Part Number: 04216

Product Description Fully synthetic fluid blended from premium polyalphaolefin

(PAO) base oils with superior additives that meet the requirements for demanding industrial hydraulic systems

within the food industry.

Applications Great for use in all types of food processing facilities.

Hydraulic Systems, vacuum pumps, canning, bearings,

valves, circulating oil.

Unit Package Description 5 Gallon Pail

Brand CRC

Generic Description 1 Hydraulic Oil

Net Fill 5 Gal

UPC Code 078254042169

Unit Dimensions 15H x 12W x 12D in

Units Per Case 1

Case Dimensions 15H x 12W x 12D in

Cases Per Pallet 36

Case Weight 38 lbs

Appearance Clear Liquid

Flash point (F) 500°F Flash point (C) 260°C

Flammability Class - CPSC Combustible

Spec Gravity Concentrate 0.84

Plastic Safe Safe on Most Plastics (Test small area)

Evaporation Rate Slow

ISO Viscosity Grade 68

SAE Grade 20

Working Temp (F) -50 to 450°F

Working Temp (C) -45.6 to 232.2°C

NSF Category Code H1

NSF Number 144418

Last revised: 1/31/2017

Page 1 of 2



and adheres to the strictest guidelines for quality in all facets of research, development and production.


CRC®, K&W®, Sta-Lube®, Marykate® and
products denoted with ® and ™ are trademarks

of CRC Industries, Inc.

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified



PRODUCT DATA SHEET



 VOC % (Federal)
 0


 VOC g/ L (Federal)
 0

VOC Lbs./ Gal. (Federal) 0

VOC Category Not Regulated

Removal (How To) Remove with Petroleum Distillates.





Last revised: 1/31/2017

Page 2 of 2