



# Tradies Choice – Acoustic Adhesive

## DESCRIPTION

**Tradies Choice WB Acoustic Adhesive** is a premium high performance acrylic based adhesive designed for the installation of commercial and domestic sheet vinyl. It has excellent plasticizer resistance and is formulated to provide quick initial grab and exhibit excellent 're-bond' characteristics.



## SURFACE PREPARATION

All surfaces to be bonded should be dry, smooth, and free of any contaminants that may affect final bond. All surfaces must be prepared in accordance with current Australian Standards 1884

Floor Coverings Resilient Sheet including moisture testing. It is recommended that all highly absorbent sub floors be primed with Master primer prior to the application of adhesive. The minimum sub floor temperature prior to commencing preparation or adhesive application is 10°C.



## DIRECTIONS FOR USE

Apply adhesive using a 3.2mm x 3.2mm x 3.2mm "V" notched spreader. Coverage should be in the vicinity of 2m<sup>2</sup> per litre. Some domestic sheet vinyl may require a fine 1.6mm x 0.8mm x

0.8mm "U" notched trowel to prevent adhesive 'show through'. Adhesive can be allowed to tack-up prior to placing the floor covering into the wet film of adhesive. Tack-up time will depend on atmospheric conditions. Always ensure complete transfer of adhesive to the floorcovering has occurred. Complete installation according to manufacturer's instructions. Roll installation on completion with the recommended weight roller. Do not allow heavy traffic for 24 hours.

## CLEAN UP

Clean tools immediately after use with warm soapy water.



## TYPICAL PROPERTIES

Base: Acrylic  
Solids: Approximately 70%  
Shelf Life: 12 months in sealed container at 20°C Packaging:



## PACKAGING

15ltr Bucket.



## CAUTION

Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

SDS is available from [www.sas-aa.com.au](http://www.sas-aa.com.au)



**SAS Australasia Pty Ltd**  
**1300 202 894**  
**[www.sas-aa.com.au](http://www.sas-aa.com.au)**

ABN: 83 617 827 282

P1 1.9.21

Disclaimer: The information supplied is to the best of SAS knowledge and is true and accurate. The application of the product is beyond SAS control and any alleged failure or damage must be inspected by a representative from SAS. All workman ship must be carried out in accordance with AS 3958.1-2007.