



Tradies Choice – Master Primer

Tradies Choice Master Primer

DESCRIPTION

Tradies Choice Master Primer is a fast-drying water based acrylic primer.
Used for porous and non-porous substrates such as existing tiles, Vinyl and carpet and vinyl adhesive residue.
Can be used over old water based paints (not to be used over oil based paints.)



SURFACE PREPERATION

The surface must be clean, dry firm and free of dust oil, grease, wax and curing compounds. The substrate must be install according to the relevant standards and manufacturer recommendations. All porous surfaces must be primed with SAS Master Primer. For non -porous surfaces such as existing tiles, adhesives must be primed using SAS Master Primer neat. Please contact SAS Technical Team for further information.

APPLICATIONS

Porous:

Priming of porous substrates such as concrete f/c sheet dilute Master primer 3 parts water to 1-part Master Primer.
Apply primer by roller or brush making sure the entire area is primed.
Allow to cure for 25 minutes before tiling or waterproofing.

Non-Porous

Priming of non-porous substrates such as existing tiles clean the tiles with sugar soap and then clean before applying the Master Primer neat.
Once the Master Primer is cured which is approximately 2 hours @ 23 °C you can apply a levelling compound or Tile adhesive.

COVERAGE

Porous substrate: 9m² per Litre
Non-Porous substrate :6m² per Litre



SAS Australasia Pty Ltd
1300 202 894
www.sas-aa.com.au

ABN: 83 617 827 282

Disclaimer: The information supplied is to the best of SAS knowledge and is true and accurate. The application of the product is beyond SAS control and any alleged failure or damage must be inspected by a representative from SAS. All workman ship must be carried out in accordance with AS 3958.1-2007.



Tradies Choice – Master Primer

PACKAGING

- Master Primer is available in 1L,5L containers.

Precautions

- Do not apply Master Primer on substrates subject to rising damp.
- Do not apply Master Primer on tiles that have wax or any other containments.

Technical Data

- **Appearance** – Orange liquid

SDS is available from www.sas-aa.com.au



SAS Australasia Pty Ltd
1300 202 894
www.sas-aa.com.au
ABN: 83 617 827 282

P2
Date:1.10.17

Disclaimer: The information supplied is to the best of SAS knowledge and is true and accurate. The application of the product is beyond SAS control and any alleged failure or damage must be inspected by a representative from SAS. All workman ship must be carried out in accordance with AS 3958.1-2007.