

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark PROTECH® AIR DUSTER



Dy-Mark PROTECH® Air Duster is a dry, multi-purpose cleaner for the safe removal of dust and lint from all delicate precision equipment. It has a powerful burst of compressed gas which will remove dirt without any abrasion risk. It is non-corrosive and leaves no residue or condensation. Ideal for off-site servicing when compressed air not available.

DIRECTIONS FOR USE

Recommended Uses:

Circuit boards, precision electronic equipment, keyboards, cameras, telephones, printers, videos and other uses.

Application:

De-activate and isolate equipment before use. Do not use on Energised equipment. Spray can in **UPRIGHT** position only. **Do not shake can during use.** Spray can in short bursts. Spray onto surface from a distance of 15-20cms. Use extension tube for hard to reach areas.

TECHNICAL DATA

Size:	235g Aerosol
Colour:	Clear
Consistency:	Colourless liquefied gas
Propellant:	HFC 152A (1,1 – Difluoroethane)

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.