

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au




Dy-Mark MINE MARKING NON-FLAMMABLE



Dy-Mark Mine Marking Non-Flammable is a layout marker specifically formulated for use in underground mines and fire sensitive situations. **Mine Marking Non-Flammable** utilizes a 360 degree valve and is available with two nozzle options for upright/ inverted or horizontal spray applications. Horizontal features a standard paint nozzle (for where the main application is side walls) whilst vertical is designed for marking ceilings and floors. For high ceilings and hard to reach areas, use of the Dy-Mark Mine Marking height extension handle is recommended (suitable for use with both options). The bright colour range provides clear and distinguishable marks on all surfaces.

Two nozzle options available:



DIRECTIONS FOR USE

Suitable Surfaces:

Rock, dirt and gravel.

Ideal Application Temperature:

Between -10°C and 40°C.

Before Spraying:

SHAKE can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake the can occasionally during use.

Application:

Hold the can **UPRIGHT** or in the **INVERTED** position and spray with the nozzle approximately 20-25cm from the surface. Adjust the spray width by moving closer or further away from the surface to be sprayed.

Drying Time:

5 minutes (25°C).

Coverage:

Approximately 2-4m² per can (depending on the surface).

Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



TECHNICAL DATA

Size:	400g Aerosol
Colour:	4 Standard and 3 Fluoro Colours
Finish:	Matt
Consistency:	Liquid
Propellant:	Tetrafluoroethane / Carbon Dioxide

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Store in a well ventilated place.

DISPOSAL

Dispose of contents/container according to regional regulations.

FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available for download from our website www.dymark.com.au or from following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.