

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark SPRAY WRITER



Dy-Mark Spray Writer is a toluene-free, reduced toxicity making paint with low odour and is ideal for all natural and cut timber applications. Utilising a 360° valve for any angle application, Spray Writer is suited for the forestry, timber processing and construction industries.

DIRECTIONS FOR USE

Suitable Surfaces:

Natural and cut timber, concrete, masonry and bitumen.

Ideal Application Temperature:

Between 5°C and 40°C. Avoid use in windy conditions.

Before Spraying:

Shake can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake the can occasionally during use.

Application:

Hold the can **UPRIGHT** or in the **INVERTED**, (upside down), position and spray with the nozzle approximately 15-25cm from the surface. Adjust spray width by moving closer or further away from the surface to be sprayed.

Coverage:

Approximately 2m² per can (depending on the surface).

Drying Time:

Dry in 10 minutes (25°C).

TECHNICAL DATA

Size:	350g Aerosol
Colour:	8 Standard and 6 Fluoro Colours
Finish:	Matt
Consistency:	Liquid
Propellant:	Hydrocarbon / Dimethyl Ether

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.