

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



Dy-Mark TURF MASTER



Dy-Mark Turf Master is a quick drying marking paint specially formulated for temporary application to grass without killing the roots. Turf Master is ideal for a range of applications such as landscaping, sporting grounds and golf courses. A separate nozzle is available making Turf Master also suitable for use by hand.

DIRECTIONS FOR USE

Suitable Surfaces:

Grass.

Ideal Application Temperature:

Between 10°C and 40°C. Avoid use in windy conditions.

Before Spraying:

SHAKE can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake the can occasionally during use.

Application:

For **INVERTED USE** only. Insert can into the **Dy-Mark Line Master** machine's spot marking handle. Ensure the nozzle is correctly seated. To achieve the narrowest line width, the spot marking handle must be inserted into the lowest position. Line width can be increased by raising the handle in the slot. Line width can be adjusted approximately 60-100mm. Test line width on cardboard sheet until desired width is achieved. Masking wheels are designed to sharpen the lines by catching any overspray at the edges only.

Coverage:

Will produce 80-100m in a 50mm continuous line, or cover 4-6 m².

Drying Time:

Touch dry in 10 minutes (25°C).

After Spraying:

Prevent blocking by holding the can **UPRIGHT** and spraying until only clear gas escapes. Also **wipe spray tip** of nozzle clean.

Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



TECHNICAL DATA

Size:	500g Aerosol
Colour:	White
Finish:	Matt
Consistency:	Liquid
Propellant:	Dimethyl Ether

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in a well ventilated place.

DISPOSAL

Dispose of contents/container according to regional regulations.

FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available for download from our website www.dymark.com.au or from following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au



DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.