

PAVER ENHANCING SEALER



STAIN-PROOF® Paver Enhancing Sealer offers both rich color enhancement and water and liquid protection through a patented combination of silicone technology. The result is a long-lasting, penetrating oil and water repellent that deepens and enriches the natural color of concrete pavers, cement tiles, terrazzo floors, and cement surfaces.



TYPICAL APPLICATIONS

Paver Enhancing Sealer works on most concrete pavers, cement tiles, terrazzo floors, and cement surfaces.

Paver Enhancing Sealer is suitable for indoor and outdoor applications and for residential and commercial buildings.

BENEFITS

- For Man-Made Stone Pavers
- Intense Color Enrichment With Oil And Water Repellency
- Fully Impregnating With No Sheen Or Shine
- Does Not Affect Slip Rate - Slip Testing (ANSI37.1)

STORAGE

Store in a well-ventilated place. Keep cool and locked up. IN CASE OF FIRE: Use alcohol resistant foam or normal protein foam for extinction.

DISPOSAL

Dispose of contents in accordance with applicable local/national/regional/international regulations.

CONTENTS

Hexyldecyltrimethoxysilane, methanol, and dimethicone.

VOC CONTENT

VOC (CALCULATED): < 200g/L

PACK SIZE

32 fl OZ/.95L		150852
1 Gallon/3.79 L		150812
2.5 Gallon/9.46 L		150832

HOW TO USE

1. **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST and allow a 24-hour cure time to check results.**
2. Ensure surfaces to be treated are dry, clean and free of residues and the surface temperature is between 40 - 95°F (5 - 35°C).
3. Using a low-pressure hand sprayer, foam roller, or similar, apply one or more even coat(s). Avoid contact with surrounding areas. Additional coats may be applied at minimum 30 minute intervals.
4. Estimated total application rate: 1 quart per 80 sq.ft. (8 sq.m.) Application rate will vary depending on surface absorption and number of coats.
5. Remove all excess then after 30 minutes a 2nd coat may be applied.
6. If sprayed, product must be backrolled into surfaces before 30 minute dwell on all coats.
7. Clean equipment with acetone.
8. Protect from moisture (e.g. rain) for a minimum of 12 hours. Surface may be used with care 12 hours after application.

TIPS FOR APPLYING ON VERTICAL SURFACES: Product dwell time is significantly lower on vertical surfaces as opposed to horizontal surfaces. For that reason, a liquid sealer will run down the wall if a substantial amount is applied. As sealers require plenty of dwell time to sufficiently penetrate the surface, apply 3 to 4 light coats of STAIN-PROOF Paver Enhancing Sealer as opposed to 2 generous coats. Apply each successive coat before the previous one dries (wet on wet, with approximately 10 minutes between coats). Place tarp or plastic sheets below to catch the excess drips.

NOTE: STAIN-PROOF Paver Enhancing Sealer will not prevent etching from acidic liquids, or physical surface wear. The level of enhancement will depend on the type of material being treated. A test on a sample piece is advised before applying the product to your surface. Eventually, wear and tear, as well as cleaning, will affect the enhancement and sealing performance. Reapplication of the product will be needed. Once enhanced, the treated surface cannot be restored back to the original look.

CAUTIONS

DANGER: Causes serious eye irritation. May damage fertility or the unborn child. **PRECAUTIONS:** Do not handle until all safety precautions have been read and understood. Wear eye protection/face protection. Keep container tightly closed. Avoid release to the environment. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

If exposed or concerned get medical advice. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

COUNTRY OF MANUFACTURE

MADE IN THE USA WITH GLOBALLY SOURCED MATERIALS



FOR MORE INGREDIENT INFORMATION, TECHNICAL DOCS, APPLICATION TIPS & COVERAGE GUIDE, SCAN THIS CODE OR VISIT: STAIN-PROOF.COM



150 Dascomb Rd,
Andover, MA 01810
USA
1866 667 5119

30-32 Assembly Drive
Tullamarine, Vic, 3043
Australia
1800 786 617

TRANSPORT

Shipping name: Non Dangerous Goods

COVERAGE GUIDE

Surface Type	sq ft/qt**	m ² /L**
Brick	80	8
Poured Concrete - Smooth	80	8
Concrete Paver (dry pressed)	80	8
Saltillo	80	8
Terracotta	80	8
Cement Tile	80	8

** Minimum Coverage rates as each surface has different absorption rates.
Check with your supplier



150 Dascomb Rd,
Andover, MA 01810
USA
1866 667 5119

30-32 Assembly Drive
Tullamarine, Vic, 3043
Australia
1800 786 617