

# COVERAGE GUIDE



## GENERAL SEALING

Premium Impregnating Sealer,  
Waterbased Penetrating Sealer,  
Premium Waterborne Impregnating  
Sealer, Color Enhancing Sealer

Paver Enhancing Sealer - 80°F for all man-made material



## COUNTERTOPS

Dense Stone Impregnating  
Sealer, Waterborne Dense  
Stone Sealer



## SALTWATER/FREEZE THAW PROTECTION

40SK Consolidator  
& Water Repellent



## PORCELAIN & QUARTZ

Porcelain & Quartz  
Sealer

	SQUARE FT PER QT**	m <sup>2</sup> /L**	SQUARE FT PER QT**	m <sup>2</sup> /L**	SQUARE FT PER QT**	m <sup>2</sup> /L**	SQUARE FT PER QT**	m <sup>2</sup> /L**
Basalt - Porous	70	7						
Basalt - Dense	120	12	120	12				
Bluestone (USA)	60	6	60	6				
Brick	60	6	60	6	50	5		
Poured Concrete - Smooth	75	7.5	75	7.5	60	6		
Poured Concrete	70	7	70	7				
Concrete Paver (dry pressed)	40	4	40	4	40	4		
Concrete Paver (wet cast)	70	7	70	7	60	6		
Coral Stone	50	5	50	5	50	5		
Granite Flamed	60	6	60	6	50	5		
Granite Honed	80	8	80	8				
Granite Polished	120	12	120	12				
Grout Lines	1000 LINEAR FT	305 LINEAR METRES			1000 LINEAR FT	305 LINEAR METRES		
Limestone Honed - Dense	70	7	70	7	60	6		
Limestone Honed - Porous	50	5			60	6		
Limestone Polished	100	10	100	10	50	5		
Limestone around salt water								
Marble Honed	100	10	100	10	*	*		
Marble Polished	150	15	150	15				
Porcelain - Honed and Polished							400	40
Quartz							400	40
Quartzite	100	10	100	10				
Saltillo	50	5	50	5				
Sandstone (Indian, hard)	70	7	70	7	50	5		
Sandstone (soft)	40	4	40	4	40	4		
Sandstone around salt water					40	4		
Slate - Dense black	120	12	120	12	*	*		
Slate	70	7	70	7				
Terracotta dense	70	7	70	7				
Terracotta porous	50	5	50	5	50	5		
Terrazzo	100	10	100	10				
Travertine honed	70	7	70	7	60	6		
Travertine polished	100	10	100	10				
Travertine around salt water					*	*		
Encaustic Tile	55	5.5			50			

\* Check with Stain-Proof representative for preferred solution

\*\* Minimum Coverage rates as each surface has different absorption rates. Check with your supplier