Safety Data Sheet ULTRABOND ECO 380

Safety Data Sheet dated: 14/03/2023 - version 5

Date of first edition: 03/05/2017



Section 1: Identification

GHS Product identifier

Mixture identification:

Trade name: ULTRABOND ECO 380

Trade code: 9019434

Recommended use of the chemical and restrictions on use

Recommended use: Water-borne synthetic polymer based adhesive

Uses advised against: Data not available.

Supplier's details

Company: MAPEI AUSTRALIA Pty Ltd

180 Viking Drive Wacol QLD 4076 Australia

T. +61 7 32765000 (Mon-Fri 8am to 4.30pm)

F. +61 7 32765076

Responsable: sales@mapei.com.au

Emergency phone number

Australian Poisons Information Centre 24 Hour Service 13 11 26

Police or Fire Brigade 000

Section 2: Hazard(s) identification

Classification of the Hazardous chemical

The product is not classified as hazardous according to Australia WHS 2 (2021).

Adverse physicochemical, human health and environmental effects:

No other hazards

GHS label elements, including precautionary statements

The product is not classified as hazardous according to Australia WHS 2 (2021).

Other hazards which do not result in a classification

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

Section 3: Composition and information on ingredients

Substances

no data available

Mixtures

Mixture identification: ULTRABOND ECO 380

Hazardous components within the meaning of the "Australian Work Health and Safety (WHS)" regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥25 - <50 %	calcium carbonate	CAS:1317-65-3 EC:215-279-6		
≥5 - <10 %	free crystalline silica (Ø >10 μ)	CAS:14808-60-7 EC:238-878-4		
≥1 - <2.5 %	1-Phenoxypropan-2-ol	CAS:770-35-4 EC:212-222-7	Eye Irrit. 2A, H319	01-2119486566-23-XXXX

Section 4: First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Wash with plenty of water and soap.

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 1 of 8

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Symptoms caused by exposure

no data available

Medical attention and special treatment

no data available

Section 5: Firefighting measures

Suitable extinguishing media

None in particular.

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: no data available

Explosive properties: ==

Oxidizing properties: no data available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

HazChem Code/Emergency Action code

N.A.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

Section 7: Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Section 8: Exposure controls and personal protection

Control parameters - exposure standards, biological monitoring

Community Occupational Exposure Limits (OEL)

OEL Country Occupational Exposure Limit Type

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 2 of 8

calcium carbonate CAS: 1317-65-3

OSHA Long Term: 15 mg/m3

OSHA Long Term: 5 mg/m3
National GREECE Long Term: 10 mg/m3
National GREECE Long Term: 5 mg/m3
National BELGIUM Long Term: 10 mg/m3
National CZECH Long Term: 10 mg/m3

REPUBLIC

National HUNGARY Long Term: 10 mg/m3
National ESTONIA Long Term: 10 mg/m3
National ESTONIA Long Term: 5 mg/m3
National SLOVAKIA Long Term: 10 mg/m3

National UNITED Long Term: 10 mg/m3; Short Term: 30 mg/m3

KINGDOM

National UNITED Long Term: 10 mg/m3; Short Term: 12 mg/m3

KINGDOM

National UNITED Long Term: 4 mg/m3; Short Term: 30 mg/m3

KINGDOM

National BULGARIA Long Term: 10 mg/m3
National ROMANIA Long Term: 10 mg/m3
National CROATIA Long Term: 4 mg/m3
National CROATIA Long Term: 10 mg/m3
National FRANCE Long Term: 10 mg/m3

free crystalline silica (Ø >10 ACGIH

1)

CAS: 14808-60-7

Long Term: 0,025 mg/m3

A2 - Suspected Human Carcinogen; lung cancer; pulmonary fibrosis

National AUSTRALIA Long Term: 0,05 mg/m3
National BELGIUM Long Term: 0,1 mg/m3
National BULGARIA Long Term: 0,07 mg/m3
National CROATIA Long Term: 0,1 mg/m3
National CZECH Long Term: 0,1 mg/m3

REPUBLIC

National DENMARK Long Term: 0,3 mg/m3

DENMARK, inhalable aerosol inhalable aerosol

National DENMARK Long Term: 0,1 mg/m3

DENMARK, respirable aerosol respirable aerosol

National DENMARK Long Term: 0,3 mg/m3 National DENMARK Long Term: 0,1 mg/m3 National ESTONIA Long Term: 0,1 mg/m3 National FINLAND Long Term: 0,05 mg/m3 National FRANCE Long Term: 0,1 mg/m3 National HUNGARY Long Term: 0,15 mg/m3 National LITHUANIA Long Term: 0,1 mg/m3 National NORWAY Long Term: 0,3 mg/m3

Totalstøv (total dust); K: Kjemikalier som skal betraktes som kreftfremkallende. (K:

Chemicals to be treated as carcinogenic.)

ACGIH Long Term: 0,025 mg/m3

(R), A2 - Pulm fibrosis, lung cancer

National PORTUGAL Long Term: 0,025 mg/m3 National ROMANIA Long Term: 0,1 mg/m3

National SLOVAKIA Long Term: 0,1 mg/m3; Short Term: 0,5 mg/m3

National SLOVENIA Long Term: 0,1 mg/m3
National SPAIN Long Term: 0,05 mg/m3
National SWEDEN Long Term: 0,1 mg/m3

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 3 of 8

National SWITZERLAN Long Term: 0,15 mg/m3

)

Predicted No Effect Concentration (PNEC) values

1-Phenoxypropan-2-ol

CAS: 770-35-4

Exposure Route: Fresh Water; PNEC Limit: 0,1 mg/l

Exposure Route: Marine water; PNEC Limit: 0,01 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0,38 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0,038 mg/kg

Derived No Effect Level (DNEL) values

1-Phenoxypropan-2-ol CAS: 770-35-4

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 42 mg/kg; Consumer: 21 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 25,7 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 3,65 mg/kg

Appropriate engineering controls

no data available

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; AS/NZS 2161.10:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Not needed for normal use.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to AS/NZS 1715-1716 for information on selection and use of appropriate respiratory protection equipment.

no data available

Section 9: Physical and chemical properties

Physical state: Liquid Appearance: paste Color: Beige

Odour: Characteristic

pH: 9.00

Melting point / freezing point: no data available
Initial boiling point and boiling range: 100 °C (212 °F)

Flash point: no data available Evaporation rate: no data available Flammability (Solid, Gas) no data available

Lower and upper explosion limit/flammability limits: no data available

Vapour pressure: no data available Vapour density: no data available Relative density: 1.23 g/cm3 Solubility in water: dispersible Solubility in oil: insoluble

Partition coefficient (n-octanol/water): no data available

Auto-ignition temperature: no data available Decomposition temperature: no data available

Kinematic viscosity: no data available

VOC % (Volatile Organic Compound): 17 (Rule 1168) g/l

Particle characteristics:

Particle size: no data available

 Print date
 14/03/2023
 Production Name
 ULTRABOND ECO 380
 Page n.
 4 of 8

Particle size distribution: no data available Shape and aspect ratio: no data available Specific surface area: no data available

Section 10: Stability and reactivity Reactivity

Stable under normal conditions

Chemical stability

no data available

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

Section 11: Toxicological information Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation
Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

calcium carbonate a) acute toxicity LD50 Oral Rat > 5000 mg/kg

free crystalline silica (\emptyset a) acute toxicity LD50 Oral > 2000 mg/kg

>10 µ)

,

LD50 Skin > 2000 mg/kg

1-Phenoxypropan-2-ol a) acute toxicity

LD50 Skin Rabbit > 2000, mg/kg

LC50 Inhalation Rat > 5400, mg/m3 4h

Section 12: Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 5 of 8

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Data

calcium carbonate CAS: 1317-65-3 a) Aquatic acute toxicity: LC50 Fish > 10000 mg/L 96

- EINECS: 215-

279-6

a) Aquatic acute toxicity : EC50 Daphnia > 1000 mg/L 48

a) Aquatic acute toxicity: EC50 Algae > 200 mg/L 72

1-Phenoxypropan-2-ol CAS: 770-35-4 - a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96h

EINECS: 212-

222-7

a) Aquatic acute toxicity: LC50 Daphnia = 370 mg/L 48h
 a) Aquatic acute toxicity: EC50 Algae > 100 mg/L 72h

Persistence and degradability

no data available

Bioaccumulative potential

no data available

Mobility in soil

no data available

Other adverse effects

no data available

Section 13: Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

no data available

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Clean waste packaging should be recycled when possible and authorized by the authority.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

Section 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

UN number

no data available

UN proper shipping name

no data available

Transport hazard class(es)

no data available

Packing group, if applicable

no data available

Environmental hazards

no data available

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 6 of 8

Special precautions for user

ADG-Subsidiary hazards no data available

ADG-S.P.: no data available

Road and Rail (ADR-RID):

no data available

ADR-Hazard identification number: NA

Air (IATA):

no data available

Sea (IMDG):

no data available

Additional Information

no data available

HazChem Code/Emergency Action code

no data available

Section 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Australian Work Health and Safety (WHS) act and the Code of Practice on preparation of safety data sheets for Hazardous Chemicals.

AICIS: all components are listed

Section 16: Any other relevant information

Code Description

H319 Causes serious eye irritation.

Code Hazard class and hazard category Description

3.3/2A Eye Irrit. 2A Eye irritation, Category 2A

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European

Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 7 of 8

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low N.A.: Not Applicable N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

 $v P v B \colon Very \ Persistent, \ Very \ Bioaccumulative.$

WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 16. OTHER INFORMATION

Print date 14/03/2023 Production Name ULTRABOND ECO 380 Page n. 8 of 8