

ARDEX SE SILICONE

Coloured Silicone for Sanitary Installations

ARDEX SE is an acetic cure sealant for applications such as movement joints (between tiles), internal corners (tiled wall and floor) and connecting joints between tiled surface and benchtops, bath edges, cupboards, splashbacks.

LOW VOC 

JOINT WIDTH

- Max width 30mm, depth 15mm

SUITABILITY

- ARDEX SE bonds well to ceramic tiles, glass, enamel, anodized aluminium, granite, porcelain, laminated bench tops and sanitary acrylics. (Not recommended for other natural stones, e.g. marble, travertine and limestones. May cause discoloration to brass and copper).

LOCATION

- Internal, External
Use ARDEX ST as bond breaker when using with ARDEX waterproof membranes (Not suitable for continuous immersion use e.g. swimming pools)

SURFACES

- Floors, Walls

COLOURS

- See ARDEX Website for Colour Selection

COVERAGE

- Approximately 12 lineal metres per cartridge with a 5 x 5mm joint size


PACKAGING

- 310mL cartridge




ARDEX SE QUICK FACTS

- Flexible sealant for use in tile movement and connecting joints
- Colour matched to popular grout and sanitary ware
- Elastic – withstands 25% total movement of original joint width



Travertine




Alabaster




Midnight




Havana




Mudberry




Slate Grey




Todd River Sand




Buff



Olive




Macchiato




Ultra White



Charred Ash



Misty Grey



Magellan Grey



CONTACT US

1300 788 780 | www.ardexaustralia.com



Download the Ardex app
(search for 'ARDEX Australia')



SYSTEM ARDEX
PREMIUM PERFORMANCE