



# MAX BOND

## PRODUCT DATA SHEET

### M60 CARPET LATEX

#### DESCRIPTION

MAX BOND M60 Carpet Latex is a Natural Latex compound for sealing raw edges of carpet and installing felt underlay to substrates.

#### DIRECTION FOR USE

Prior to joining carpet seams with heat bond tape or seam sealer, apply MAX BOND M60 to edge of carpet and allow to dry.

Doing this helps prevent with loss of tufts and unravelling after seams have been trimmed.

When used to install felt underlay to subfloors apply a liberal amount to the subfloor and install underlay into wet latex.

#### CLEAN UP

Clean tools immediately after use with warm soapy water.

#### TYPICAL PROPERTIES

Base: Natural Latex

Appearance: White Liquid

Viscosity: Thin Liquid

Shelf Life: 12 months in sealed container at 20°C

Packaging: 1, 4 & 15 Litre

Odour: Ammonia

Freezability: Avoid freezing

*Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Material Safety Data Sheet (MSDS), available on MJS web site*

*Updated 11/03/21*



**QUEENSLAND**  
**Brisbane**  
MJS Floorcoverings  
35 Dividend St  
Mansfield 4122  
Ph: 07 3347 7300  
Fax: 07 3343 9792

**NSW**  
**Sydney**  
MJS Floorcoverings  
2/4-7 Potter Close  
Wetherill Park 2164  
Ph: 02 9616 1500  
Fax: 02 9616 1502

**VICTORIA**  
**Melbourne**  
MJS Floorcoverings  
82 Endeavour St  
Sunshine 3020  
Ph: 03 9351 7400  
Fax: 03 9351 7402

**TASMANIA**  
**Hobart**  
MJS Floorcoverings  
101 Albert Rd  
Moonah 7000  
Ph: 03 6242 8800  
Fax: 03 6242 8802

**NORTHERN TERRITORY**  
**Darwin**  
MJS Floorcoverings  
Unit 4/124 Coonawarra Rd  
Winnellie NT 0821  
Ph: 08 7922 9700  
Fax: 08 7922 9702

**SOUTH AUSTRALIA**  
**Adelaide**  
MJS Floorcoverings  
22 Ridley Street  
Hindmarsh SA 5007  
Ph: 08 8178 5300  
Fax: 08 8178 5302

**WESTERN AUSTRALIA**  
**Perth**  
MJS Floorcoverings  
Opening soon