




## ULTIMATE EXTREME PRESSURE CYCLE CHAIN LUBRICANT

**SpeedX®** is the ultimate, extreme performance lubricant whose additives chemically react with metal surfaces and subsurfaces to virtually eliminate wear while providing the lowest coefficient of friction measurable. SpeedX provides long-lasting, heat- and load-resistant lubrication, decreases wear and extends the useful life of treated items and parts. Skateboards, roller skates, chains and derailleurs will all operate smoother, quieter, with greater efficiency and last longer when treated with SpeedX.

SpeedX thrives under high rpm, heavy loads and high temperatures! Waxes and other lubricating oils are displaced by moisture or worn away by pressure – so their effectiveness is quickly diminished. Not so with SpeedX! SpeedX bonds with metal and metal alloys on the molecular level, and clings tenaciously like a magnet. SpeedX releases the surface tension of moisture, displaces it and maintains its fantastic lubricating capability in all conditions.

The exotic additive package in SpeedX is activated by triboenergy (the heat energy of friction), either external or internal (frictional heating), and causes the surface and subsurface of the metal to be modified. The modified surface becomes both smoother, allowing for the transition to hydrodynamic lubrication more easily, and intrinsically possesses a lower coefficient of friction. And like all products in the CorrosionX family, SpeedX's protection against rust and corrosion is unmatched.


Dulux Auckland laboratory  
constant salt spray test  
according to industry  
standard ASTM B-117.  
Pics taken after 72 hrs.  
Download the entire  
test report from  
[www.corrosionx.com](http://www.corrosionx.com)



Muc Off Wet Lube



Muc Off Hydro Dynamic



INOX Chukka Chain Lube MX9



SpeedX



Rock'n Roll



Finish Line bike chain lube



Squirt

### TECHNICAL SPECIFICATIONS

- Film Thickness: 0.4 mil
- Neutral Salt Fog: >336 hours\*  
ASTM B117
- Humidity Cabinet: >1,320 hours\*  
ASTM D1748
- Dielectric Strength: >30,000 volts typ.  
ASTM D877
- Anti-Wear: 0.242mm\*\*  
ASTM D4172
- Coefficient of Friction: 0.044\*\*\*  
ASTM D4172
- Load Carrying: 750 lbs.  
ASTM 2625 Method B
- Flash Point coc: >270°F
- Volatile Organic Content: 0%
- Storage Stability: indefinite

\* Note: Sand blasted mild steel panel. 0 - <1% surface rust.

\*\* Note: The smaller the number, the better the performance.  
A standard lubricating oil of the same viscosity would yield a value of 1.0 - 1.2 mm.

\*\*\*Note: The lowest coefficient of friction measurable on lubricated steel surfaces.

### POLAR BONDING TECHNOLOGY INSIDE

