


TECHNICAL BULLETIN



ENVIROSHIELD COATINGS

19 Motivation Drive Wangara, WA, 6065 AUSTRALIA

T +61 8 9302 4000 | FREE 1800 999 196 | F +61 8 9302 5000

CONSOLIDATOR PLUS

COMBINATION CONSOLIDATOR & SEALER

WARNING
Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.

Avoid breathing fumes/mist vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.
IF ON SKIN: Wash thoroughly. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Move person to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a POISON CENTRE or doctor/physician if you feel unwell.

EMERGENCY INFORMATION:
FIRE: Use foam, CO2, dry powder fire extinguishers.
SPILLS: Absorb spillage with inert material. Absorb with sawdust or other absorbent material. Prevent entry into drainage systems, rivers. Transfer into clean labelled drums. Dispose of according to local government regulations.
Additional information is found in the Material Safety Data Sheet.
In an emergency call your local police on 000 or 112.

ENVIROSHIELD COATINGS
19 Motivation Drive, Wangara, WA 6065
Ph: (08) 9302 4000

CONSOLIDATOR PLUS
COMBINATION CONSOLIDATOR & SEALER

Consolidator Plus is a consolidating/penetrating sealer developed to prevent salt attack around swimming pools and soft masonry surfaces. It is a premium natural look penetrating sealer for internal/external surfaces and will not change the slip factor. Not suitable for bluestone. Always test first.

CONTAINS <10% Ethyl Silicates, >60% 2-Ethylhexanol

ENVIROSHIELD COATINGS

Batch No:

APPLICATION: Apply a light coat to a clean, dry masonry surface, wipe runs off any vertical surfaces. It is ESPECIALLY IMPORTANT to apply to all surfaces including underneath the pool coping. Apply the second coat when the first coat is dry, generally between 1-4 hours depending on ambient conditions. A minimum of 2 coats to be applied and more porous surfaces require more coats. Apply by lambswool applicator, paint brush or low pressure garden sprayer. Soft porous surfaces will require more coats. Allow 7 days curing time. Clean up all equipment with Cyclone.

COVERAGE: Approx. 10 sq mtrs per litre, per coat.

NET CONTENTS

<input type="checkbox"/> 2 L		<input type="checkbox"/> 10 L	
<input type="checkbox"/> 20 L		<input type="checkbox"/> 200 L	

MATERIAL & FUNCTION

CONSOLIDATOR PLUS is a consolidating/ penetrating sealer developed to prevent salt attack around swimming pools and soft masonry surfaces. It is a premium natural look penetrating sealer for internal/external surfaces and will not change the slip factor. Not suitable for bluestone. This is a low VOC product (less than 5%). **Consolidator Plus** may change the colour slightly.

APPLICATIONS

Suitable For: Sandstone, Dense Limestone, Porcelain, Granite, Masonry and porous Vitrified Tiles. Always test first.

DIRECTION FOR USE

Apply a light coat of **Consolidator Plus** to a clean dry masonry surface, wipe runs off vertical surfaces. It is ESPECIALLY IMPORTANT to apply to all surfaces including underneath the pool coping. Apply the second coat when the first coat is dry, generally between 1-4 hrs depending on ambient conditions. A minimum of two coats to be applied and more porous surfaces require more coats. Apply by lambswool applicator, paint brush or low pressure garden sprayer. Allow 7 days curing time. Clean up all equipment with Cyclone. Reseal every 12 months.

COVERAGE

Best results are obtained using a minimum of two coats. A total of 1L of **CONSOLIDATOR PLUS** is required to cover approx.5 square metres with two coats.

CAUTION

Avoid contact with skin and eyes and avoid breathing vapour or spray mist.
This product is not flammable but is combustible. Keep away from sources of ignition.
Consult the Material Safety Data Sheet for further information.

PACKAGING

2 Litre, 10 Litre, 20 Litre and 200 Litre containers

IMPORTANT NOTICE TO CUSTOMER

Since the use of this product is beyond the control of either seller or manufacturer, their only obligation shall be to replace any quantity of product which is proven defective. They cannot assume any risk or liability in excess of the purchase price of the product itself, which does not include labour or any consequential damages resulting from the use of this product. Determining the suitability of this product for any intended use shall be solely the responsibility of the user.

ALWAYS TEST FIRST.

[F:\TECHBULL\CONSOLIDATOR PLUS.DOC.](#)