


SUPABORD - CONTRACTOR GRADE TEMPORARY FLOOR PROTECTION SPECIFICATION SHEET



DESCRIPTION

SupaBord Contractor Grade is our Heavy Duty premium temporary floor protection product for commercial, residential construction and renovation projects.

SupaBord Contractor Grade is the latest technology in floor protection, providing a balance of vapour permeability, durability and strength. Developed to withstand the demands of the construction industry, each roll is conveniently sized at approximately 800mm wide x 37m long x 1mm thick, covering 30 sqm.

SupaBord Contractor Grade is flexible yet strong and made from 100% recycled material. SupaBord Contractor Grade prevents the risk of damage and rework, saving money on material and labour costs and is the brand of choice by contractors worldwide.

FEATURES



SPILL RESIST



QUICK FIT



BREATHABLE



HEAVY DUTY



100% RECYCLED



CUT & FOLD

INSTALLATION INSTRUCTIONS

1. Ensure the subfloor (base floor) is clean and dry
2. Remove paper wrap from the SupaBord roll
3. Roll out SupaBord over the flooring area or surface, logo side facing up
4. Cut SupaBord to length with a utility knife, ensuring the seams are neat and fit well together
5. Tape the SupaBord butt joints, long joints and perimeter with SupaBord Joint Tape. *Do not apply SupaBord Joint Tape to floor surfaces as it may affect some finishes*
6. Apply SupaBord Edge Tape to the outside perimeter of the flooring area



SupaBord
Bord Industries HK Ltd
Suite 1106-8, 11/F, Tai Yau Building,
181 Johnston Road, Wanchai, Hong Kong
sales@supabord.com.au | www.supabord.com



SUPABORD - CONTRACTOR GRADE TEMPORARY FLOOR PROTECTION MATERIAL SAFETY DATA SHEET



PRODUCT & COMPANY IDENTIFICATION

Distributor Name:
Bord Industries HK Ltd
Suite 1106-8, 11/F, Tai Yau Building,
181 Johnston Road, Wanchai, Hong
Kong

Product information contact:
sales@supabord.com.au

MSDS information contact:
sales@supabord.com.au

Product name:
SupaBord Contractor Grade
Temporary Floor Protection

Issue Date: June 2016

Product description:
Gypsum liner paper and various
chip
board – 100% recycled

AVAILABLE SIZE

Colour: Natural
Roll Size: Approximately 800mm
wide x 37m long x 1mm thick,
covers 30 sqm
Roll Weight: Approximately 18kg
(39.6lbs)

PRODUCT SPECIFICATIONS

Thickness	1mm (approx.)
Density:	3.26 – 3.31
Mullen Burst:	140 p.s.i.
Taber Stiffness MD:	1703.7 gf/cm
Taber Stiffness CD:	647.6 gf/cm
Caliper	
Low Spec:	44.01
Target Spec:	45.03
High Spec:	46.02
Basis Weight	
Low Spec:	140.90
Target Spec:	143.97
High Spec:	147.05
Moisture	
Low Spec:	4.05%
Target Spec:	6.00%
High Spec:	7.50%

USES

SupaBord Contractor Grade provides ideal protection for granite, marble, stone, coloured concrete, tile, wood, carpet and linoleum. It provides excellent protection for a variety of surfaces including walls, bench tops and stairs.

HANDLING AND STORAGE

No special handling requirements. Keep away from flammable and combustible material. Paper products will not release hazardous chemicals under normal conditions of use.

SAFETY

Upon review of relevant OSHA regulations and the characteristics of paperboard, a MSDS is not required because paperboard falls within the exemptions for a 'manufactured article' and 'wood products'.

DISCLAIMER

Reasonable care has been taken in preparation of this document. The information in this document was obtained from sources, which we believe reliable. Bord Industries HK Ltd extends no warranties and makes no representations as to the expressed or implied accuracy or completeness of the information contained therein. We do not assume or accept responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. We disclaim all liability for any harmful health effects, which may be caused by misuse of our products.