


SUPABORD 150 DAY BREATHABLE EDGE TAPE SPECIFICATION SHEET



DESCRIPTION

SupaBord 150 Day Breathable Edge Tape is one of two tapes in the SupaBord product range.

SupaBord 150 Day Breathable Edge Tape is specifically designed to secure SupaBord Temporary Floor Protection to floors and walls for up to 150 days. SupaBord Edge Tape is made from quality crepe paper with a natural rubber adhesive to provide instant attachment to a wide variety of surfaces.

FEATURES

- Joins SupaBord Temporary Floor Protection edges to surfaces
- Strong and flexible
- Low to medium 150-day contractor grade adhesive
- Convenient size 48mm wide x 50m long x 1.2mm thick

INSTALLATION INSTRUCTIONS

1. Peel back the edge of **SupaBord Edge Tape** and begin to unroll
2. Tape the SupaBord edges to the floor with **SupaBord Edge Tape**
3. Simultaneously apply firm pressure and smooth down the tape
4. Carefully cut the end with a utility knife
5. When finished, fold the edge of the tape back against the roll to use at a later time
6. To remove, roll up tape and discard




SupaBord

Bord Industries HK Ltd
Suite 1106-8, 11/F, Tai Yau Building,
181 Johnston Road, Wanchai, Hong Kong

sales@supabord.com.au | www.supabord.com



SUPABORD 150 DAY BREATHABLE EDGE TAPE MATERIAL SAFETY DATA SHEET



PRODUCT & COMPANY IDENTIFICATION

Distributor Name:

Bord Industries HK Ltd
Suite 1106-8, 11/F, Tai Yau Building,
181 Johnston Road, Wanchai, Hong Kong

Product information contact:

sales@supabord.com.au

MSDS information contact:

sales@supabord.com.au

Product name: SupaBord 150 Day Breathable
Edge Tape

Issue Date: June 2016

PRODUCT SPECIFICATIONS

Total thickness	0.12mm
Backing	Crepe Paper
Adhesive type	Rubber and solvent based
Adhesion to steel	27N/100mm
Tensile Strength MD	333N/100mm
Backing Weight	58g/m ²
Temperature (ideal)	21° Celsius (70° Fahrenheit)
Humidity (ideal)	50%
Elongation	7%
Chemical Family	Saturated paper backing, natural rubber and resins solvent based adhesive
Trade Name	SupaBord 150 Day Breathable Edge Tape
Material Use	Light to medium duty tape

AVAILABLE SIZE

Colour: White **Roll Weight:** 150g

Roll Size: 48mm wide x 50m long x 0.12mm thick

HANDLING AND STORAGE

We recommend safe storage in a cool, dry place.

Store at room temperature from 15° to 25° Celsius (59° to 77° Fahrenheit) with a maximum humidity of 65%. Keep out of direct sunlight exposure. Product shelf life and storage is 12 months. If SupaBord Edge Tape is stored in extreme conditions over 35° Celsius (95° Fahrenheit) or below 4.5° Celsius (40° Fahrenheit), allow the product to return to room temperature prior to use.

Like most tapes, avoid taping directly to finished surfaces. We recommend undertaking a sample test on the curing floors prior to use.

USES

SupaBord Edge Tape is specifically designed to secure SupaBord Temporary Floor Protection to floors and walls for up to 45 days. SupaBord Edge Tape is made from quality crepe paper with a natural rubber adhesive to provide instant attachment to a wide variety of surfaces.

DISCLAIMER

Reasonable care has been taken in preparation of this document. The information in this document was obtained from sources, which we believe reliable. Bord Industries HK Ltd extends no warranties and makes no representations as to the expressed or implied accuracy or completeness of the information contained therein. We do not assume or accept responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. We disclaim all liability for any harmful health effects, which may be caused by misuse of our products.

© 2011 SupaBord, Bord Industries HK Ltd. All rights reserved for product names and attributes registered.

SAFETY

Hazard Identification

Eye Contact:

Eye contact is not expected during normal use. Eye irritation including redness, cornea scratching and tearing may occur.

First Aid Measure:

Immediately flush eyes with large amounts of water. In the case of an emergency, seek immediate medical attention.

Fire Fighting Measures

Extinguishing Methods:

Water spray, Carbon Dioxide, dry power agent

Special Procedures:

Full protective equipment and self-contained breathing apparatus

Exposure Controls

Eye Protection: Avoid eye contact

Ventilation: Ventilated environment

Fire and Explosion Avoidance: Avoid flames

Physical and Chemical Properties

Appearance: Solid, white

Flammability: Combustible

Water Vapour Transmission: Permeability not less than 500g/m²

