

# SLIPSO<sup>®</sup>VE

ECO FRIENDLY

## NON SLIP TREATMENT



### SURFACE TREATMENT INDUSTRIES

5 Mareno Road Tullamarine VIC 3043

T 1300 282 282 F 03 9334 2621

E [info@sti.net.au](mailto:info@sti.net.au)

**Please visit our website  
to locate distributors  
in your area.**

**[www.sti.net.au](http://www.sti.net.au)**

**For your safety, ensures that with  
just a simple application, slippery  
surfaces become safer!**

**SlipSolve<sup>®</sup>** can be applied to all mineral surfaces including: ceramics, concrete, marble, terrazzo, and enamel. The process does not materially alter the nature of a surface.

- SOLVENT-FREE & 98% BIODEGRADABLE
- ECO FRIENDLY & NON HAZARDOUS
- WATER-BORNE, NON TOXIC & SAFE TO USE



**SlipSolve®** is a revolutionary heavy-duty invisible lasure (not a film) specially formulated to reduce the risk of slips that does not contain acids and does not materially alter the surface. It provides a tough, clear, anti-slip impregnation that will not de-laminate on a variety of surfaces including: ceramic, concrete, marble, terrazzo, enamel, brick, slate, clay pavers, sandstone and many other surfaces.

**SlipSolve®** also protects the surface from ingress of water, oil and other pollutants making the surfaces easier to clean, resistant to erosion and the build-up of dirt and grime.

Whilst **SlipSolve®** will enhance the safety of porcelain surfaces, all smooth floor surfaces regardless of treatment are potentially dangerous when proper care is not taken.



**WHERE TO USE** – Factories, commercial areas, nursing homes, entrance halls, gymnasiums, swimming pool surrounds, pedestrian crossings, bars, restaurants, kitchens, shower units, bath tubs and anywhere floors are slippery, especially when wet.

**GLOSS LEVEL** – Applies wet and dries invisible. On some surfaces the gloss level may be reduced marginally, it is highly recommended a trial area is treated prior to the entire surface. To achieve optimum safety some substrates gloss reduction will be necessary.

**PREPARATION** – Clean surface to be treated with STICleaner to ensure the surface is free of oil, grease, dust or other contaminants.

### APPLICATION

1. Remove any protective wax from substrate surface.
2. Pour or spray the product onto clean and dry surface applying it with the assistance of a brush or a low-pressure spray.
3. Make sure the product stays present over the complete surface during the treatment. Add product if necessary.
4. Do not let the product dry or bead during the whole treatment time
5. After treatment, rinse carefully with water.
6. The treated surface can be used immediately.

- **FOR CONCRETE, TERRAZO, TILES, MARBLE AND POLISHED GRANITE:** To be used undiluted (allow to react for 40-60 minutes).
- **FOR POLISHED PORCELAIN TILES:** use SlipSolve Porcelain, specifically formulated for polished porcelain.

### CLEAN UP WITH – Water

## Try our other products



### DeckLast®

Protection for Wood Surfaces



### EffGuard®

Restore Masonry Surfaces



### STICleaner®

Removes Oil, Grease, Pollution and Other Stains from Masonry Surfaces



### NuSeal®

Protection for Concrete, Natural Stone and Masonry Surfaces



### TexGuard

Protection for Textile Fabrics, Leather and Carpet



### RenderSeal

Protection for Rendered Surfaces