

Poultice Plus

Ready to Use Cleaner For

- | | | |
|-----------------------|--------------------|------------------|
| ■ Sanded Grout | ■ Non-sanded Grout | ■ Mortar |
| ■ Ceramic Tile | ■ Quarry Tile | ■ Porcelain Tile |
| ■ Clay Pavers | ■ Marble | ■ Limestone |
| ■ Travertine | ■ Granite | ■ Slate |
| ■ Other Natural Stone | | |

Special Features

- | | | |
|-----------------|--------------|---------------|
| ■ Non Acid | ■ Non Bleach | ■ Fast Acting |
| ■ User Friendly | | |

PRODUCT DESCRIPTION

KEEP OUT OF REACH OF CHILDREN. **Poultice Plus** is an easy to use, fine, non acidic absorption powder. **Poultice Plus** is effective in removing stains that are deep into the substrate. **Poultice Plus** can be effective when used with "distilled water" or many other chemical additives, see the **Miracle Sealants' Stain Removal Guide**. **Poultice Plus'** absorptive action draws out most stains from within the substrate with little or no effort or technical know how necessary.

Sample Testing

Due to the differences of each substrate, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Protect Neighboring Surfaces

Always protect neighboring surfaces including masonry, wood, carpet, metal, landscaping and other non masonry surfaces.

APPLICATION INSTRUCTIONS

Read entire label and SDS/PDS before using.

All previous applied sealers, coatings and/or waxes must be removed using **Mira Strip** or **Finish Sealer Stripper** as directed.

Mix **Poultice Plus** with "distilled water" or appropriate chemical to form a peanut butter like paste. The paste should be pliable but not runny. Apply the paste directly to the stain approximately 1/4" - 1/2" thick. Overlap the stain by approximately 1/4" - 1/2". Cover the paste with plastic wrap and tape the plastic with "non marking" tape to create an airtight seal. Allow the paste to dry completely, approximately 24 - 48 hours. Remove the plastic wrap and scrap the dried paste from the substrate with a non scratching utensil like a plastic putty knife or spatula. Rinse off all residue with clean "distilled water". If the stain is lighter but not completely removed repeat the same procedures. It may be necessary to use multiple applications to remove some stains.

Some stains can be removed more easily by mixing the appropriate chemical with **Poultice Plus**. Refer to the **Miracle Sealants Company Stain Removal Guide** for additional information.

Heavy Duty Cleaning: Use **Phosphoric Acid Cleaner**, **HDAC** or **Liquid Poultice** as directed.

Light Cleaning: Use **Tile & Stone Cleaner**, **Grout Cleaner**, **Porcelain & Ceramic Tile Cleaner**, **Limestone/Travertine Soap** or **Counter Kleen** as directed.

Color and Gloss Enhancement

For added color with "Textured and Non polished" surfaces, **511 Seal & Enhance** or **Mira Matte** may be used. For porous type "Pavers", **511 Seal & Enhance** may be used as directed.

Polish Enhancement

Periodically use **Mira Dust**, **Marble Conditioner** or **Granite Brite** as directed.

Water, Stain & Slip Protection

To protect cleaned area from future soiling and staining and increase static coefficient of friction, we recommend applying the appropriate **Miracle Penetrating Sealer/Impregnator**.

Coverage

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **Poultice Plus** will clean approximately 5 - 10 square feet per 1 pound container.

MAINTENANCE

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide**. Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

Storage

Store **Poultice Plus** in the original upright container, properly sealed and unmixed. Stored at 77° F (25° C), **Poultice Plus** has no shelf life. Do not allow to freeze.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
 1-626-443-6433 or 1-800-350-1901 • Fax: 1-626-443-1435
 website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact
 Info Trac @ 1-800-535-5053

Additional Products

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

Caution

Store in cool area. Only use this product in well ventilated areas. Good ventilation means that fresh air is flowing in such a way to feel a slight breeze. Continue to ventilate until odors are completely eliminated. Avoid contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surface has thoroughly dried. **Refer to the SDS for additional information.**

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.