

Acoustic Supplies Pty Ltd

ABN: 61 264 776 209
28 Norton Street
Randwick NSW 2031
Australia
Ph: 0414 281 800 Fax: 02 9326 4893

Technical Data & Information Sheet

10th October 2017

Vibramat – 3mm 100% Rubber

General Description

Vibramat is made from Recycled Tyres and Waste Rubber. They are firstly granulated and sieved to the correct granule size before being blended with a water resistant PU polymer. It is then put into a mould to compress and set at the right density, after which, sliced into the correct thickness and made to size.

Visual Description

Black in colour, with colourful speckles of waste rubber. The surface texture is of small granules of rubber bonded together to form a flat sheet. The thickness is 3mm, and if seen in a full sheet, should measure 1.1m x 1.1m.

Packaging

All Vibramat products come in pallets that allow every sheet of material to sit flat for the ease of installation. The pallets are then strapped firmly for safe and neat transportation. They can be stacked during warehousing (please check with local safety restriction on stacking of pallets).

330-sheet pallet = (330 x 1.1 x 1.1) = 399.3sqm. Approximate weight is 1030Kg

Specification

Density: 850- 900Kg/m³

Thickness: 3mm

Size of Sheet: 1.1m x 1.1m

Warranty

This product when used as an acoustic underlay where the substrate is firm and relatively flat would be warranted for 10 years.

If you require further information not covered in this data sheet, please contact: Acoustic Supplies on the above numbers or email

Info@acousticsupplies.com