

Acoustic Supplies Pty Ltd

ABN: 61 264 776 209
28 Norton Street
Randwick NSW 2031
Australia
Ph: 0414 281 800 Fax: 02 9326 4893

Technical Data & Information Sheet

10th October 2017

Vibramat – 5mm 100% Rubber

General Description

Vibramat is made from Recycled Tyres and Waste Rubber. They are firstly granulated, sieved to the correct granule size and type before being blended with a water resistant PU polymer. It is then pressed to the correct density and sliced to the required thickness.

Visual Description

The surface texture of very fine granules of rubber bonded together to form a flat sheet. The colour can vary, but mostly black with speckles of coloured granules from the waste rubber component. The thickness is 5mm, and if seen in a full sheet, should measure 1.1m x 1.1m.

Packaging

Vibramat comes in pallets that allow every sheet of material to sit flat for the ease of installation. The pallets are then strapped firmly for safe and neat transportation. They can be stacked several pallets high during warehousing (please check with local safety restriction on stacking of pallets).

200-sheet pallet = (200 x 1.1 x 1.1) = 242sqm. Approximate weight is 850Kg.

Specification

Density: 700- 850Kg/m³

Thickness: 5mm

Size of Sheet: 1.1m x 1.1m

Warranty

This product when used as an acoustic underlay where the substrate is firm and relatively flat would be warranted for 10 years.

If you require further information not covered in this data sheet, please contact Acoustic Supplies on the above numbers or email
info@acousticsupplies.com