

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au

Dy-Mark

Dy-Mark PROTECH® FREEZE SPRAY



Dy-Mark PROTECH® Freeze Spray is an efficient cooling system that instantly freezes surfaces to -50 degrees C. Its powerful blast of propellant instantly chills suspect electrical and electronic components. It is non-flammable, plastic safe, leaves no residue and is non-abrasive. Is also ideal for removing chewing-gum or sweets from fabrics.

DIRECTIONS FOR USE

Recommended Uses:

Thermostats, computers, thermometers, circuit boards, laboratory and precision electronic equipment, office equipment and more uses.

DO NOT SPRAY ON SKIN. Can will dispense freezing liquid which can cause frostbite on exposed skin. Shake can well.

Application:

Spray can in **UPRIGHT** position only. Spray onto surface from a distance of 10-15cms. Spray in short bursts. Use extension tube for hard to reach areas.

TECHNICAL DATA

Size: 300g Aerosol

Colour: Clear

Consistency: Colourless Liquid

Propellant: HFC134 A (1,1,1,2 – Tetra fluoroethane)

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au

Dy-Mark

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.