

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066

Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au

Dy-Mark

Dy-Mark PROTECH® HEAVY DUTY DEGREASER



Dy-Mark PROTECH® Heavy Duty Degreaser has been specially formulated to provide effective and fast removal of tough grease, oil, dirt and grime. It delivers a concentrated jet which works immediately on contact and is easy to rinse off with water. For use on tools, machinery and equipment.

Uses a 360° valve for upright inverted applications.

DIRECTIONS FOR USE

Recommended Uses:

Engines, Machinery, Lifts and Hoists, tools, industrial equipment, farm equipment, Lawn mowers, garage floors and other uses.

Application:

Shake can well. Shake can occasionally during use. 360 degree valve enables spraying in upright and inverted positions. Do not spray at 45 degree angle. Hold can 20 - 25cms from surface. Spray liberal coating directly on to surface, saturating the problem area. Allow to penetrate for 5 - 10 minutes.

Hose off with pressure. Heavy or thick deposits may have to be loosened with a scraper or brush. Repeat application if necessary.

Prolonged exposure to painted metal surfaces not recommended.

TECHNICAL DATA

Size:	400g Aerosol
Colour:	Light Yellow
Consistency:	Liquid
Propellant:	Carbon Dioxide

STORAGE

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL

Dispose of contents/container according to regional regulations.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd

PO Box 1556 Toowong 4066


Phone: 1300 396 275 Fax: 1300 360 440

www.dymark.com.au

Dy-Mark

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Dy-Mark; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark Sales and Customer Support Centre on 1300 396 275.