

Prep & Maintenance Cleaner

High concentrate, non-toxic alkaline based cleaner
Ideal for pre-application and daily maintenance
cleaning of Stellmann Coatings and other surfaces

Article Code: K 805-005



Features

Stellmann Prep & Maintenance Cleaner is a heavy duty, alkaline concentrated detergent for the removal of light and heavy soil and grease. The powerful, low foaming formula allows for mechanical and manual floor cleaning. It removes soiling from ceramic and porcelain tiles, vinyl, linoleum, natural stone, concrete and metals. It is also perfect as an economical and effective solution to keep Stellmann Coatings clean. Shelf life: 1 year upon delivery.

Pre-Application Instructions

Dilute Stellmann Prep & Maintenance Cleaner from a ratio of 1 : 10 up to 1 : 20 parts with water, depending on the degree of soiling. This corresponds to a usage of approx. 100 to 200ml of the diluted Stellmann Cleaner mixture per square meter. Hot water is best.

Apply Cleaner dilution to surface, allow to soak and scrub. After scrubbing, use a mop, squeegee or wet and dry vacuum cleaner to clean up residue. Make sure to rinse twice with plenty of cold, clear water and dry surface. Check if surface is clean, then continue with the Stellmann Installation.

Maintenance Cleaning Of Stellmann Coating

This is a concentrated formulation for economical use. For normal soiling, dilute Stellmann Prep & Maintenance Cleaner from a ratio of 1:100 up to 1:200 parts with water (5 to 10ml in 1L of water). Hot water is best. Refer to Stellmann Technical Advice & Maintenance Instructions for full cleaning instructions. Do not use rough brushes, steel wool, and other abrasive cleaning tools. Cleaning machines can be used with soft/medium brushes. Never use any kind of pads on cleaning machines. Do not use hard brushes, scrubbing pads and other abrasive pads.

- Apply cleaner dilution to surface, allow to soak. Use a cleaning method (e.g. mop, broom brush, cleaning machine, etc.) compliant to the Stellmann Technical Advice & Maintenance Instructions.
- Use a squeegee, wet and dry vacuum cleaner or vacuum function on cleaning machine to clean up residue. *Do not skip this step as this is the most important step of any cleaning procedure.*
- Now rinse with plenty of cold, clear water
- Make sure to dry surface

Heavy Soiling

Heavy local soiling can be removed with a brush/scrubber and a higher concentration of Stellmann Prep & Maintenance Cleaner. For advice or in case of doubt contact Stellmann Pty Ltd via info@stellmann.com.au.

- Start with a 1:10 dilution in hot water.
- Apply Cleaner dilution to surface, scrub in using a circular movement and allow to soak for 2 minutes.
- After scrubbing, squeegee or wet and dry vacuum cleaner to clean up residue.
- Make sure to rinse twice with plenty of cold, clear water or until all foaming stops.
- Dry surface. Check if surface is clean and repeat when improvement is seen.
- Use a higher concentration if needed of 5:1 or 1:1. If this does not work, reach out to Stellmann Pty Ltd for advice.