

Compliant stair nosings. Without the strips.

Create durable, slip-resistant stair nosing strips or demarcation lines on ceramic and porcelain tiles, concrete, marble, travertine, vinyl, metal and glass, toward AS 1428.1 and AS 4586.

No drilling, no gluing

A cost-effective, hassle-free alternative to metal or plastic strips. Application is quick and straightforward, and the coating can be overcoated for touch-ups.

P4 or P5, in three colours

Durable, UV-resistant and slip-rated P4, or P5 with Stellmann particles. Traffic White (RAL 9016), Traffic Black (RAL 9017) and Traffic Yellow (RAL 1023) for contrast that meets AS 1428.1.

Fully removable

Need it gone? The coating comes off completely with Stellmann Paint & Coating Stripper, without damaging the substrate.



Stellmann Stair Nosing Coating, 900 gram pack.



White stair nosings rolled straight onto curved bluestone steps. No strips, no drilling.

Fast to lay down. Built to be walked on.

60 min

Touch dry in approximately 60 minutes, trafficable in 24 hours.

2 hours

Pot life once mixed, depending on temperature and humidity.

P4 / P5

Slip-rated finish; P5 with Stellmann Non-Slip Particles added.



Application

Roller or HVLP sprayer, by any competent tradesperson. The Aqualine PU PRO system underneath means excellent chemical and mechanical resistance on stairs that work for a living.



Where it goes

Stair treads and nosing strips, demarcation lines, platform edges and walkway markings, indoors and out.



Colours

- Traffic White, RAL 9016
- Traffic Black, RAL 9017
- Traffic Yellow, RAL 1023



Traffic Yellow treads, top to bottom of a commercial stairwell.

Contact us for a consultation and a FREE SAMPLE.

1300 987 095 · info@stellmann.com.au · stellmann.com.au