

Four steps keep your Stellmann floor performing for years.

A simple, regular program keeps the surface at its best and keeps the Stellmann warranty valid.



1. Clean on a regular program

Set the frequency by traffic and area. High-traffic zones and greasy areas such as commercial kitchens need daily cleaning. P3 Soft and P3 surfaces take a mop or microfiber mop; P4 and P5 need a microfiber cloth, broom brush, or a cleaning machine with a brush.



2. Use the right tools and cleaner

Use Stellmann Prep & Maintenance Cleaner, diluted per the label, with warm water. Machines take soft or medium brushes only, never pads. Avoid acids, solvents (methylated spirits, alcohol, acetone), chlorine, sodium and abrasive detergents. Keep disinfectant dwell time under 10 minutes.



3. Rinse after cleaning

Rinse thoroughly with plenty of clean, cold water. This neutralises any cleaners or contaminants left on the surface.



4. Remove residue after rinsing

Remove excess water with a squeegee, wet/dry vacuum, or the drying function on a cleaning machine. Never let the surface air-dry, or residual contaminants build up on it.



Stellmann Prep & Maintenance Cleaner

5L alkaline based concentrate, for pre-application and daily cleaning. Stellmann's industry leading warranty stays valid when the surface is regularly cleaned with it. For a copy of the warranty, contact info@stellmann.com.au.

Protecting your Stellmann coating.

DO	DON'T
Regularly clean	Don't use solvents, spirits, alcohol, sodium or chlorine (bleach)
Regularly inspect	Don't rub the surface excessively
Clean in mild conditions	Don't use hard brushes, scrubbing pads, or other abrasive tools
Rinse with clear water and actively dry the surface after cleaning	Don't use "dirt-blaster" functions on pressure washers



Cleaning machines

Soft or medium brushes only. There is no such thing as a soft pad; every pad is abrasive. For seating and dining areas, all chair and furniture contact points must have soft felt pads installed: screw-in soft felt pads for commercial projects, and replace any pad that comes off.



High pressure cleaning

Keep at least 30cm from the surface and stay under 60 Barr. Never use "dirt-blaster" functions; they can damage the surface.



If dirt builds up

Skipping the squeegee or vacuum step lets dirt build up over time. If that happens, do a deep-clean and contact us to adjust your regimen.

What to expect, and where we draw the line.

12 hours

Curing time for light foot traffic.

5 days

Full chemical cure. Chemical and mechanical cleaning possible after five days.

The limits, in plain words

The coatings have excellent chemical resistance but are not designed for submerged areas. They are water-repellent, but neither designed nor intended to solve water-proofing issues: the warranty is void where water comes through the surface from underneath, and Stellmann is not responsible for identifying water-proofing issues. Efflorescence, and whatever causes it, must be resolved before installation. The warranty is also void if the product is misused or the cleaning instructions are not strictly followed.



Advice line, 7 days

Our friendly team can help simplify the specification process, saving you time and money by providing the right advice for your project. Call 1300 987 095 or email info@stellmann.com.au.

Keep the warranty on your side.

Clean regularly with Stellmann Prep & Maintenance Cleaner and follow the four steps.

1300 987 095 · info@stellmann.com.au · stellmann.com.au